














Railway Anti-Vibration Backplane Modules

For 2.5" HDD/SSD SAS 12G Compatible



Specs\Model No	JJ-47SS	JJ-87SS	JJ-127SS
Picture(black)	  12G	  12G	  12G
Picture(back view)			
Form Factors	1*5.25 Bay for 4*2.5" HDD(SSD) 1 x MiniSAS HD [SFF-8643]	2*5.25 Bay for 8*2.5" HDD(SSD) 2 x MiniSAS HD [SFF-8643]	3*5.25 Bay for 12*2.5" HDD(SSD) 3 x MiniSAS HD [SFF-8643]
Support HDD types	1) For 2.5" HDD or SSD 2) For SAS III HDD(SSD) 3) For SAS 12G or SAS 6G HDD 4) Supported HDD height upto 14.5mm		
Interface	1 x MiniSAS HD [SFF-8643]	2 x MiniSAS HD [SFF-8643]	3 x MiniSAS HD [SFF-8643]
Hot swap	YES	YES	YES
Power Connector	15pin power connector x 1	15pin power connector x 2	15pin power connector x 3
Keylock/anti shock	* With metal keylock * With guiding rail for anti-vibration design		
Anti-vibration	With anti-vibration springs on the HDD tray		
Transfer rate	Support Upto SAS 12Gbps(SAS-III)		
HDD Connection	Cableless HDD connection	Cableless HDD connection	Cableless HDD connection
Material	Aluminum body & carrier & aluminum front bezel		
Air Ventilation	*Front ventilating holes 40 x 40 x20mm fan x 2	*Horizontal PCB design for easy air flowing 70 x 70 mm fan x 1	*Rear cooling fan 80 x 80 mm fan x 1
Power LED	Power ON : Blue		
Fan Failure LED	YES	*Fan failure : Red blinking(slow) LED indication	
Overheating LED	YES	*Overheating : Red blinking(fast) LED indication	
Data cable	w/o cables [*Optional MiniSAS HD to MiniSAS HD cable (70cm)]		
Product Colors	Black	Black	Black
Dimension	202(L) x 146(W) x 42(H)mm	198(L) x 146(W) x 85(H)mm	203(L) x 146(W) x 127(H)mm
Weight	0.95 kgs	1.35 kgs	1.85 kgs
<div></div> <div>SAS 12G & SAS 6G 2.5" Railway Anti-vibration Multi-bay Series</div>			