

smartctl 5.43 2012-06-30 r3573 [FreeBSD 8.3-RELEASE-p5 amd64] (local build)  
Copyright (C) 2002-12 by Bruce Allen, <http://smartmontools.sourceforge.net>

=== START OF INFORMATION SECTION ===

Device Model: WDC WD10EZRX-00A8LB0  
Serial Number: WD-WMC1U6178752  
LU WWN Device Id: 5 0014ee 6ad5e90f5  
Firmware Version: 01.01A01  
User Capacity: 1,000,204,886,016 bytes [1.00 TB]  
Sector Sizes: 512 bytes logical, 4096 bytes physical  
Device is: Not in smartctl database [for details use: -P showall]  
ATA Version is: 8  
ATA Standard is: Exact ATA specification draft version not indicated  
Local Time is: Mon Oct 21 20:29:21 2013 CEST  
SMART support is: Available - device has SMART capability.  
SMART support is: Enabled

=== START OF READ SMART DATA SECTION ===

SMART overall-health self-assessment test result: PASSED

General SMART Values:

Offline data collection status: (0x82) Offline data collection activity  
was completed without error.

Auto Offline Data Collection:

Enabled.

Self-test execution status: ( 0) The previous self-test routine  
completed

without error or no self-test has

ever

been run.

Total time to complete Offline  
data collection: (13320) seconds.

Offline data collection  
capabilities:

(0x7b) SMART execute Offline immediate.

Auto Offline data collection on/off

support.

Suspend Offline collection upon new  
command.

Offline surface scan supported.

Self-test supported.

Conveyance Self-test supported.

Selective Self-test supported.

SMART capabilities:

(0x0003) Saves SMART data before entering  
power-saving mode.

Supports SMART auto save timer.

Error logging capability:

(0x01) Error logging supported.

General Purpose Logging supported.

Short self-test routine

recommended polling time:

( 2) minutes.

Extended self-test routine

```
recommended polling time:      ( 152) minutes.
Conveyance self-test routine
recommended polling time:      (   5) minutes.
SCT capabilities:              (0x30b5) SCT Status supported.
                                SCT Feature Control supported.
                                SCT Data Table supported.
```

SMART Attributes Data Structure revision number: 16

### Vendor Specific SMART Attributes with Thresholds:

ID#	ATTRIBUTE_NAME	FLAG	VALUE	WORST	THRESH	TYPE	UPDATED
1	Raw_Read_Error_Rate	0x002f	200	200	051	Pre-fail	Always
-	0						
3	Spin_Up_Time	0x0027	136	134	021	Pre-fail	Always
-	4183						
4	Start_Stop_Count	0x0032	100	100	000	Old_age	Always
-	136						
5	Reallocated_Sector_Ct	0x0033	200	200	140	Pre-fail	Always
-	0						
7	Seek_Error_Rate	0x002e	200	200	000	Old_age	Always
-	0						
9	Power_On_Hours	0x0032	100	100	000	Old_age	Always
-	352						
10	Spin_Retry_Count	0x0032	100	100	000	Old_age	Always
-	0						
11	Calibration_Retry_Count	0x0032	100	100	000	Old_age	Always
-	0						
12	Power_Cycle_Count	0x0032	100	100	000	Old_age	Always
-	136						
192	Power-Off_Retract_Count	0x0032	200	200	000	Old_age	Always
-	41						
193	Load_Cycle_Count	0x0032	200	200	000	Old_age	Always
-	865						
194	Temperature_Celsius	0x0022	116	107	000	Old_age	Always
-	27						
196	Reallocated_Event_Count	0x0032	200	200	000	Old_age	Always
-	0						
197	Current_Pending_Sector	0x0032	200	200	000	Old_age	Always
-	0						
198	Offline_Uncorrectable	0x0030	200	200	000	Old_age	Offline
-	0						
199	UDMA_CRC_Error_Count	0x0032	200	200	000	Old_age	Always
-	0						
200	Multi_Zone_Error_Rate	0x0008	200	200	000	Old_age	Offline
-	0						

SMART Error Log Version: 1

No Errors Logged

SMART Self-test log structure revision number 1

No self-tests have been logged. [To run self-tests, use: smartctl -t]

SMART Selective self-test log data structure revision number 1

SPAN	MIN_LBA	MAX_LBA	CURRENT_TEST_STATUS
1	0	0	Not_testing
2	0	0	Not_testing
3	0	0	Not_testing
4	0	0	Not_testing
5	0	0	Not_testing

Selective self-test flags (0x0):

After scanning selected spans, do NOT read-scan remainder of disk.

If Selective self-test is pending on power-up, resume after 0 minute delay.