

ASUS uses cookies and similar technologies to perform essential online functions, analyze online activities, provide advertising services and other functions. For detailed information, please visit "[Cookies and similar technologies](#)".

[Cookie Settings](#)
[Accept Cookies](#)
[Products](#)
[What's Hot](#)
[ProArt](#)
[Commercial](#)
[Service](#)

X99-E WS

CPU

Build in Intel® Socket 2011-v3 Core™ i7/Core™ i7 X-Series Processors

Supports Intel® 22 nm CPU

Supports Intel® Turbo Boost Technology 2.0

* The Intel® Turbo Boost Technology 2.0 support depends on the CPU types.

Intel® Socket 2011-v3 for Intel® Xeon® processor E5-1600 v3 product family

Intel® Socket 2011-v3 for Intel® Xeon® processor E5-2600 v3 product family

Intel® Socket 2011-v3 for Intel® Xeon® processor E5-1600 v4 product family

Intel® Socket 2011-v3 for Intel® Xeon® processor E5-2600 v4 product family

Chipset

Intel® X99

Memory

8 x DIMM, Max. 128GB, DDR4 3200(O.C.)/3000(O.C.)/2800(O.C.)/2666(O.C.)/2400(O.C.)/2133 MHz Non-ECC, Un-buffered Memory *1

8 x DIMM, Max. 128GB, DDR4 2400/2133/1866 MHz ECC, Un-buffered Memory *2

8 x DIMM, Max. 256GB, DDR4 2400/2133/1866 MHz ECC, Register Memory *2

Quad Channel Memory Architecture

Supports Intel® Extreme Memory Profile (XMP)

* Hyper DIMM support is subject to the physical characteristics of individual

CPUs.

* Refer to www.asus.com for the Memory QVL (Qualified Vendors Lists).

Multi-GPU Support Supports NVIDIA® 4-Way SLI™ Technology
Supports AMD 4-Way CrossFireX Technology

Expansion Slots **40-Lane CPU-**

7 x PCIe 3.0/2.0 x16 (single x16 or dual x16/x16 or triple x16/x16/x16 or quad x16/x16/x16/x16 or seven x16/x8/x8/x8/x8/x8/x8)

28-Lane CPU-

7 x PCIe 3.0/2.0 x16 (single x16 or dual x16/x16 or triple x16/x16/x16 or quad x16/x16/x16/x16 or seven x16/x8/x8/x8/x8/x8/x8)

Storage **Intel® X99 chipset : *3**

1 x SATA Express port, gray, , Compatible with 2 x SATA 6.0 Gb/s ports

1 x M.2 x4 Socket 3, gray, , with M Key, type 2260/2280 storage devices support (PCIe mode)

8 x SATA 6Gb/s port(s), gray, *4

Intel® Rapid Storage Technology supports*5

ASMedia® SATA Express controller : *6

1 x SATA Express port, gray, , Compatible with 2 x SATA 6.0 Gb/s ports

ASMedia® SATA 6Gb/s controller :

2 x eSATA 6Gb/s port(s), Compatible with 2 x SATA 6.0 Gb/s ports

LAN **Intel® I210-AT, 1 x Gigabit LAN Controller(s)**

Intel® I218LM, 1 x Gigabit LAN, Dual interconnect between the Integrated Media Access Controller (MAC) and Physical Layer (PHY)

Audio Realtek® ALC1150 8-Channel High Definition Audio CODEC featuring Crystal Sound 2

- Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, Front Panel MIC Jack-retasking
- High quality 109 dB SNR stereo playback output (Line-out at rear) and 104 dB SNR stereo playback input (Line-in)
- High-fidelity audio OP AMP(s)

Audio Feature :

- DTS Ultra PC II
- DTS Connect
- Optical S/PDIF out port(s) at back panel
- BD Audio Layer Content Protection
- Audio Shielding: Ensures precision analog/digital separation and greatly reduced multi-lateral interference
- Dedicated audio PCB layers: Separate layers for left and right channels to guard the quality of the sensitive audio signals
- Audio amplifier: Provides the highest-quality sound for headphone and speakers

Premium Japanese-made 12K hours capacitors

- Absolute Pitch 192khz/24bit true BD lossless sound
- Separate layer for left and right track, ensuring both sound deliver equal quality

USB Ports **Intel® X99 chipset :**

4 x USB 3.1 Gen 1 port(s) (4 at back panel, blue)

Intel® X99 chipset :

4 x USB 2.0/1.1 port(s) (4 at mid-board)

ASMedia® USB 3.1 Gen 1 controller : *7

2 x USB 3.1 Gen 1 port(s) (2 at back panel, blue)

ASMedia® USB 3.1 Gen 1 controller : *8

8 x USB 3.1 Gen 1 port(s) (4 at back panel, , 4 at mid-board)

Workstation Feature **7 x PCIe x 16 slot(s)**

ASUS Dr. Power

12K hours Capacitors

ProCool Power Connector

Q-Code Logger

Special Features **5-Way Optimization by Dual Intelligent Processors**

- Whole system optimization with a single click! 5-Way Optimization tuning key perfectly consolidates TPU, EPU, DIGI+ Power Control, Fan Xpert 3, and Turbo App together, providing better CPU performance, efficient power saving, precise digital power control, whole system cooling and even tailor your own app usages.

ASUS TPU :

- Auto Tuning
- GPU Boost
- TPU switch

ASUS EPU :

- EPU
- EPU switch

ASUS Digital Power Design :

- Industry leading Digital 8 Phase Power Design
- Industry leading Digital 4 Phase DRAM Power Design
- CPU Power Utility
- DRAM Power Utility

ASUS Exclusive Features :

- MemOK!
- AI Suite 3
- Ai Charger+
- USB Charger+
- M.2 & SATA Express
- ASUS UEFI BIOS EZ Mode featuring friendly graphics user interface
- USB 3.0 Boost
- Disk Unlocker
- Turbo LAN
- Crystal Sound 2

Remote Entertainment

- Media Streamer

ASUS EZ DIY :

- Precision Tweaker 2
- ASUS O.C. Tuner
- ASUS CrashFree BIOS
- ASUS EZ Flash
- ASUS USB BIOS Flashback®
- ASUS UEFI BIOS EZ Mode
- Push Notice

ASUS Q-Design :

- ASUS Q-Shield
- ASUS Q-Code
- ASUS Q-LED (CPU, DRAM, VGA, Boot Device LED)
- ASUS Q-Slot
- ASUS Q-DIMM
- ASUS Q-Connector

Media Streamer**Special Memory O.C. Design****Turbo App****Fan Xpert 3****Operating System Support** Windows® 10

Windows® 8.1

Windows® 8

Windows® 7

Back I/O Ports 2 x eSATA

2 x LAN (RJ45) port(s)

10 x USB 3.1 Gen 1 (blue)

1 x Optical S/PDIF out

8 x Audio jack(s)

1 x USB BIOS Flashback® Button(s)

1 x Q-Code Logger button

Internal I/O Ports 2 x USB 3.1 Gen 1(up to 5Gbps) connector(s)

support(s) additional 4 USB 3.1 Gen 1 port(s) (19-pin)

2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s)

2 x SATA Express connector: gray, Compatible with 2 x SATA 6.0 Gb/s ports

1 x M.2 Socket 3 for M Key, type 2260/2280 devices

1 x TPM connector(s)

8 x SATA 6Gb/s connector(s)

1 x CPU Fan connector(s) (1 x 4 -pin)

1 x CPU OPT Fan connector(s) (1 x 4 -pin)

4 x Chassis Fan connector(s) (4 x -pin)

1 x S/PDIF out header(s)

1 x Thunderbolt header(s)

2 x 8-pin EATX 12 V Power connector

1 x 6-pin EATX 12 V_1 Power connector(s)

1 x 24-pin EATX Power connector(s)
1 x 8-pin ATX 12V Power connector(s)
1 x EZ XMP switch
1 x Front panel connector(s)
1 x System panel(s) (Q-Connector) (Chassis intrusion header is inbuilt)
1 x DRCT header(s)
1 x MemOK! button(s)
1 x Thermal sensor connector(s)
1 x TPU switch(es)
1 x CPU/DRAM overvoltage jumper(s)
1 x Power-on button(s)
1 x Reset button(s)
1 x Clear CMOS button(s)
1 x Dr.Power switch(es)
1 x 3-pin CHASSIS(Chassis intrusion) connector
1 x COM port header

Accessories

User's manual

ASUS Q-Shield

I/O Shield

1 x COM port cable(s)
12 x SATA 6Gb/s cable(s)
1 x Supporting DVD
1 x 3-Way SLI bridge(s)
1 x 4-Way SLI bridge(s)
1 x SLI bridge(s)
1 x Q-connector(s) (2 in 1)
1 x 2-port USB 2.0 module(s)

BIOS 128 Mb Flash ROM, UEFI AMI BIOS, PnP, DMI2.7, WfM2.0, SM BIOS 2.7, ACPI 5.0, Multi-language BIOS,
ASUS EZ Flash 2, CrashFree BIOS 3, F11 EZ Tuning Wizard, F6 Qfan Control, F3 My Favorites, Quick Note, Last Modified log,
F12 PrintScreen, F3 Shortcut functions and ASUS DRAM SPD (Serial Presence Detect) memory information.

Manageability WfM 2.0, DMI 2.7, WOL by PME, PXE

Support Disc Drivers 、 ASUS Utilities 、 EZ Update 、 Anti-virus software (OEM version)

Form Factor CEB Form Factor

12 inch x 10.5 inch (30.5 cm x 26.7 cm)

Weight Color Box (3-in-1)

Net Weight : 6.02 KG

Gross Weight : 9 KG

Bulk Pack (5-in-1)

Net Weight : 7.5 KG

Gross Weight : 10.2 KG

Environment Operation temperature: 10°C ~ 35°C

Non operation temperature: -40°C ~ 70°C

Non operation humidity: 20% ~ 90% (Non condensing)

Note*1 When installing Intel® Socket 2011-v3 Core™ i7/i7 X-Series Processors

*2 When installing Intel® Xeon® E5-2600/1600 v4/v3 Processor. Memory max capacity would also depend on CPU installed.

*3 Intel® X99 Express Chipset with RAID 0, 1, 5, 10 and Intel Rapid Storage Technology 13 support

4 8 x SATA 6.0 Gb/s ports (4 x gray from controller 1, 4 x black from controller 2)

*5 These functions will work depending on the CPU installed

*6 These SATA ports are for data hard drivers only. ATAPI devices are not supported

*7 ASMedia® USB 3.0 controller- supports ASUS USB 3.0 Boost

*8 ASMedia® USB 3.0 Hubs- supports ASUS USB 3.0 Boost

- Products certified by the Federal Communications Commission and Industry Canada will be distributed in the United States and Canada. Please visit the ASUS USA and ASUS Canada websites for information about locally available products.
- All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.
- Specifications and features vary by model, and all images are illustrative. Please refer to specification pages for full details.
- PCB color and bundled software versions are subject to change without notice.
- Brand and product names mentioned are trademarks of their respective companies.
- Specifications and features vary by model, and all images are illustrative. Please refer specification pages for full details.
- *Precise specifications and features vary by model . Please refer to the specification page
- The product (electrical , electronic equipment, Mercury-containing button cell battery) should not be placed in municipal waste. Check local regulations for disposal of electronic products.
- The use of trademark symbol (TM, ®) appears on this website means that the word text, trademarks, logos or slogans, is being used as trademark under common laws protection and/or registered as Trademark in U.S. and/or other country/region.

Want More?

Who We Are

Need Help?

Community

Global / English

[Privacy Policy](#) | [Terms of Use Notice](#) | ©ASUSTeK Computer Inc. All rights reserved.