

TrueNAS® Expansion Shelves



Scale Storage Effortlessly

To meet the demands of today's applications, businesses need to keep pace with massive data growth. The modern business has to support a full range of storage protocols for Windows, Apple, Unix, and mobile devices. Thousands of terabytes of data need to be retained for analysis by Big Data applications.

To support these and other business requirements, and to reduce storage sprawl, the TrueNAS Enterprise "pay as you grow" pricing model offers storage, power, and space efficiency with the ability to expand capacity on an as-needed basis.

Five expansion shelf options make TrueNAS capacity expansion effortless. Every TrueNAS model has enclosure management, supports storage controller redundancy and global hot spares, zero downtime firmware updates, upgrades, and offers around the clock support. Without disruption, you can add expansion shelves and drives to TrueNAS to keep pace with growing storage needs.



Max Capacity

		ES12	ES24F	ES24	ES60	ES102
	Base Unit					
TrueNAS X10	250 TB	500 TB (two shelves)	500 TB (one shelf)	500 TB (one shelf)	Not Supported	
TrueNAS X20	250 TB	500 TB (two shelves)	1 PB (two shelves)	1 PB (two shelves)	1 PB (one shelf)	
TrueNAS M30	500 TB		Not Supported			Not Supported
TrueNAS M40	500 TB	1 PB (two shelves)	1 PB (two shelves)	1 PB (two shelves)	3 PB (two shelves)	
TrueNAS M50	500 TB	2 PB (eight shelves)	4 PB (eight shelves)	4 PB (eight shelves)	10 PB (eight shelves)	
TrueNAS M60	500 TB	3 PB (twelve shelves)	5 PB (twelve shelves)	5 PB (twelve shelves)	15 PB (twelve shelves)	25 PB (twelve shelves)



Expansion Shelf Lineup



Hardware Specifications

Available Expansion Shelves

TrueNAS ES12

- 2U: 12× 3.5"/2.5" hard drive bays (front-loading, hot swap)
- Redundant, hot-swap SAS3 (12 Gb/s) controllers
- 3x Mini-SAS HD Host Connections per Controller (SFF-8644)
- Physical Dimensions (L x W x H)
 - 21 × 19 × 3.5"
 - 531 × 447 × 89 mm
- Rackmount Rail Depth
 - 23.5" to 29.5" standard
 - Up to 36" with extenders (included)
- Empty weight: 26 lbs | 12 kg
- Fully-loaded weight: 44 lbs | 20 kg
- Power Draw: 112 W (idle); 180 W (max)

TrueNAS ES60

- 4U: 60× 3.5"/2.5" hard drive bays (top-loading, hot swap)
- Redundant, hot-swap SAS3 (12 Gb/s) controllers
- 2x Mini-SAS HD Host Connections per Controller (SFF-8644)
- Physical Dimensions of Shelf (L x W x H)
 - 33.38 × 19 × 6.9"
 - 848 × 483 × 176 mm
- Physical Dimensions of Shelf with Cable Management Arm (L x W x H)
 - 39.50 × 19 × 6.9"
 - 1000 × 483 × 176 mm
- Designed to fit in a standard 19" wide, 1000 mm depth cabinet
- Rackmount Rail Depth
 - 27.5" to 31" (699 to 788 mm) with Cable Management
 - Up to 38.5" (978 mm) w/o Cable Management
- Empty weight: 85 lbs | 38.5 kg
- Fully-loaded weight: 175 lbs | 80 kg
- Power Draw with 60 HDDs: 479W (idle); 821W (max)

TrueNAS ES102

- 4U: 102 × 3.5" hard drive bays (top-loading, hot swap)
- Redundant, hot-swap SAS3 (12 Gb/s) controllers
- 6x Mini-SAS HD Host Connections per Controller (SFF8644)
- Physical Dimensions of Shelf (L x W x H)
 - 41.25 × 17.61 × 6.89"
 - 1047 × 447 × 175 mm
- Physical Dimensions of Shelf with Dual Cable Management Arm (L x W x H)
 - 47.13 × 17.61 × 6.89"
 - 1197 × 447 × 175 mm
- Designed to fit in a standard EIA-310 compliant rack, 17.72" - 18.31" wide, 1200 mm deep cabinet
 - A wider cabinet allows more options for using a zeroU PDU with the enclosure
 - Narrow cabinets could require a rack-mounted PDU to properly allow the enclosure to be fully installed into the rack and properly cabled with the included Cable Management Arms
- Rackmount Rail Depth
 - 32" to 36" (813 to 914 mm) with Cable Management
 - Balance Warning: The ES102 also extends 37.4 in outward when fully extended from rack
- Rack Width: 17.72" to 18.31" (450mm to 465mm) + 1.5mm nominal hole spacing (EIA-310 standard)
- Empty weight: 70 lbs | 31.8 kg
- Fully-loaded weight: 262 lbs | 118.8 kg
- Power Draw: 1300W (typical); 1600W (max)

TrueNAS ES24

- 4U: 24× 3.5"/2.5" hard drive bays (front-loading, hot swap)
- Redundant, hot-swap SAS3 (12 Gb/s) controllers
- 3x Mini-SAS HD Host Connections per Controller SFF-8644)
- Physical Dimensions (L x W x H)
 - 20.5 × 19 × 7" | 521 × 483 × 178 mm
- Rackmount Rail Depth: 26 to 36.5"
- Empty weight: 40 lbs | 18 kg
- Fully-loaded weight: 76 lbs | 34.5 kg
- Power Draw: 231 W (idle); 288 W (max)

TrueNAS ES24F

- 2U 24×2.5" tool-less hard swap bays (front-loading, hot swap)
- Redundant, hot-swap SAS3 (12 Gb/s) controllers
- 3x Mini-SAS HD Host Connections per Controller (SFF8644)
- Physical Dimensions of Shelf (L x W x H)
 - 21.5" x 19 x 3.5" | 546 x 483 x 88 mm
- Rackmount Rail Depth: 23 to 35.75" (584mm to 908mm)
- Empty weight: 34.1 lbs | 15.5 kg
- Fully-loaded weight: 43.4 lbs | 19.7 kg
- Power Draw: 231 W (idle); 288 W (max)

Available Storage Media

- Enterprise Nearline Hard Drives (7200 RPM SAS3 - 12 Gb/s)
 - Capacities available from 4 TB to 22 TB
 - Self-Encrypting Drives (SED) Available
- Enterprise Solid State Drives (SAS3 - 12 Gb/s)
 - Capacities available from 1.92 TB to 7.68 TB
 - Self-Encrypting Drives (SED) Available

Power Management

- Redundant, hot-swappable, high efficiency (90%+) power supplies
- 100-240V 50/60Hz input power on TrueNAS ES12/ES24/ES24F ES60 (Auto-Switching)
- High-line (200-240V 50/60HZ) input power only on TrueNAS ES102
- UPS signal response and alerts
- Redundant cooling
- All expansion shelves are RoHS 6/6 compliant